

# **bizhub** c250i Color A3 multifunctional





Giving Shape to Ideas

### **CUSTOMER BENEFITS**



#### Intuitive operability Operate the bizhub like a smartphone or tablet with fully customised user interface

# **OPTIONS**



Mobile connectivity Print anytime from anywhere with Konica Minolta's innovative mobile technologies



Security Secure network integration, data encryption, hard drive overwrite, and advanced user authentication



Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



**Productivity** Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability Numerous eco features reduce energy consumption and costs

1 ENHANCED FEATURES		
PDF enhancements LK-102v3		Fax board FK-514
OCR text recognition LK-105v4		Wireless LAN UK-221
Barcode fonts LK-106		USB I/F kit EK-608
Unicode fonts LK-107		USB I/F kit EK-609
OCR A and B fonts LK-108		Fiery controller IC-420
Document converter pack LK-110v2		Interface kit VI-516
ThinPrint <sup>®</sup> client LK-111	5 bizhuberso	Interface board UK-115
Serverless pull printing LK-114		Biometric authentication AU-102
Trusted Platform Module activation		ID card reader
LK-115v2 Antivirus LK-116	4	Mount kit MK-735


3 OTHERS	4 MED
Document feeder DF-632	PC-11
Document feeder DF-714	2 x Un PC-21
Original cover OC-511	Large PC-41
Working table WT-506	Copie DK-51
<b>10-Key pad</b> KP-102	Large
Security kit SC-509	Banne BT-C1
Keyboard holder KH-102	
Air cleaning unit CU-102	

LEGEND

Mandatory option
Option

This option can only be installed with the respective option above it

MEDIA INPUT	]
<b>1 x Universal tray</b> PC-116	OF
<b>2 x Universal tray</b> PC-216	OF
Large capacity tray PC-416	
<b>Copier desk</b> DK-516x	
Large Capacity tray LU-302	
Banner tray BT-C1e	



**FINISHING FUNCTIONALITIES** 



## DESCRIPTIONS

### ENHANCED FEATURES

ENHANCED FEATURES	
LK-102v3 PDF enhancements	PDF/A(1b); PDF encryption; digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX; XLSX and PDF/A
LK-111 ThinPrint <sup>®</sup> client	Print data compression for reduced network impact
LK-114 Serverless pull printing	Secure and Follow Me printing solution
	requiring no server application
LK-115v2 TPM activation	Trusted Platform Module for protection of data
	encryption and decryption
LK-116 Antivirus	Bitdefender <sup>®</sup> Antivirus provides real time scanning
	of all incoming and outgoing data

### CONNECTIVITY

FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
IC-420 Fiery controller	Professional colour print controller
VI-516 Interface kit for IC-420	Fiery controller interface card
UK-115 Interface board for IC-420	Fiery controller interface board
AU-102 Biometric authentication	Finger vein scanner
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader

DF-632 Document feeder	Reversing automatic document feeder, capacity 100 originals
DF-714 Document feeder	Dualscan automatic document feeder, capacity 100 originals
OC-511 Original cover	Cover instead of ADF
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function (2 kits required for Dualscan ADF)
KH-102 Keyboard holder	To place USB keyboard
CU-102 Air cleaning unit	Improving indoor air quality by reduced emissions
MEDIA INPUT	
PC-116 1x Universal tray	500 sheets, A5-A3, 52-256 g/m <sup>2</sup>
PC-216 2x Universal tray	2x 500 sheets, A5-A3, 52-256 g/m <sup>2</sup>
PC-416 Large capacity tray	2,500 sheets, A4, 52-256 g/m <sup>2</sup>
LC-302 Large capacity tray	3,000 sheets, A4, 52-256 g/m <sup>2</sup>
BT-C1e Banner tray	Multipage banner feeding
	Description of the second se
DK-516x Copier desk	Provides storage space for print media and other materials
MEDIA OUTPUT	Provides storage space for print media and other materials
	Frovides storage space for print media and other materials
MEDIA OUTPUT	
MEDIA OUTPUT FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
MEDIA OUTPUT FS-533 Inner finisher PK-519 Punch kit for FS-533	50-sheet stapling, 500 sheets max. output 2/4 hole punching, autoswitching
MEDIA OUTPUT FS-533 Inner finisher PK-519 Punch kit for FS-533 FS-536 Staple finisher	50-sheet stapling, 500 sheets max. output 2/4 hole punching, autoswitching 50-sheet stapling, 3,300 sheets max. output
MEDIA OUTPUT FS-533 Inner finisher PK-519 Punch kit for FS-533 FS-536 Staple finisher	50-sheet stapling, 500 sheets max. output 2/4 hole punching, autoswitching 50-sheet stapling, 3,300 sheets max. output 50-sheets staple finisher; 20-sheets booklet finisher;
MEDIA OUTPUT FS-533 Inner finisher PK-519 Punch kit for FS-533 FS-536 Staple finisher FS-536SD Booklet finisher	50-sheet stapling, 500 sheets max. output 2/4 hole punching, autoswitching 50-sheet stapling, 3,300 sheets max. output 50-sheets staple finisher; 20-sheets booklet finisher; 2,300 sheets max. output

OTHERS

# **TECHNICAL SPECIFICATIONS**

### SYSTEM SPECIFICATIONS

STSTEIN SPECIFICATIONS	
Panel size/resolution	10.1" / 1024 x 600
System memory (standard/max)	8,192 MB
System hard drive	256 GB SSD (standard)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP;
	HTTP(S); AppleTalk; Bonjour
Automatic document feeder (optional)	Up to 100 originals; A6–A3; 35–163 g/m <sup>2</sup> ;
	RADF or Dualscan ADF available
Paper input capacity (standard/max)	1,150 sheets / 6,650 sheets
Paper tray input (standard)	1x 500 sheets; A6-A3; custom sizes; 52-256 g/m <sup>2</sup>
	1x 500 sheets; A5-SRA3; custom sizes; 52-256 g/m <sup>2</sup>
Paper tray input (optional)	1x 500 sheets; A5–A3; 52–256 g/m <sup>2</sup>
	2x 500 sheets; A5–A3; 52–256 g/m <sup>2</sup>
	1x 2,500 sheets; A4; 52–256 g/m <sup>2</sup>
Large capacity tray (optional)	1x 3,000 sheets; A4; 52-256 g/m <sup>2</sup>
Manual bypass	150 sheets; A6–SRA3; custom sizes; Banner; 60–300 g/m <sup>2</sup>
Automatic duplexing	A5-SRA3; 52-256 g/m <sup>2</sup>
Finishing modes (optional)	Offset; Group; Sort; Staple; Punch; Half-fold; Letter-fold; Booklet
Output capacity (standard)	Max. 250 sheets
Output Capacity (optional)	Max. 3,300 sheets
Stapling	Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 g/m <sup>2</sup> )
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 30 sheets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to $209 \text{ g/m}^2$ )
Booklet output capacity	Max. 100 booklets; unlimited (without tray)
Copy/print volume (monthly)	Rec. 16,000 pages; Max. <sup>1</sup> 130,000 pages
Toner lifetime	Black up to 28,000 pages
	CMY up to 28,000 pages

Imaging unit lifetime	Black up to 170,000/1,000,000 pages (drum/developer)
	CMY up to 65,000/1,000,000 pages (drum/developer)
Power consumption	220-240 V / 50/60 Hz; Less than 1.58 kW
System dimension (W x D x H)	615 x 688 x 779 mm (without options)
System weight	Approx. 84.0 kg (without options)
PRINTER SPECIFICATIONS	
Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating System	Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10 (32/64)
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android);
	Konica Minolta Mobile Print (iOS/Android/Windows 10 Mobile);
	Mobile Authentication and Pairing (iOS/Android)
	Optional: Google Cloud Print; WiFi Direct
DRIVITED ODEOLEIOATIONIC (O	PTIONAL)
PRINTER SPECIFICATIONS (O	,
Print controller	Embedded Fiery IC-420
Controller CPU	AMD GX-424CC @ 2.4 GHz
Memory/HDD	4,096 MB / 500 GB

	· · · · · · · · · · · · · · · · · · ·
Controller CPU	AMD GX-424CC @ 2.4 GHz
Memory/HDD	4,096 MB / 500 GB
Page description language	Adobe PostScript 3 (CPSI 3020); PCL 6; PCL 5c
Operating System	Windows 7 (32/64); Windows 8 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Linux

### SCANNER SPECIFICATIONS

4

Scan speed (mono/colour)	Up to 100/100 ipm in simplex
	Up to 200/200 ipm in duplex
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF;
	XPS; Compact XPS; PPTX
	Optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,100 (single + group); LDAP support

### COPIER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Simitri <sup>®</sup> HD polymerised toner
Copy/print speed A4 (mono/colour)	Up to 25/25 ppm
Copy/print speed A3 (mono/colour)	Up to 15/15 ppm
Autoduplex Speed A4 (mono/colour)	Up to 25/25 ppm
1 <sup>st</sup> copy out time A4	5.2/6.9 sec.
Warm-up time	Approx. 11 sec. in mono; 13 sec. in color <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	A6-A3; Custom sizes
Magnification	25–400% in 0.1% steps; Auto-zooming

#### FAX SPECIFICATIONS

Super G3 (optional)
Analogue; i-Fax; Colour i-Fax; IP-Fax
Up to 600 x 600 dpi
MH; MR; MMR; JBIG
Up to 33.6 Kbps
2,100 (single + group)

#### Type of system boxes Secure print; Encrypted PDF print; Fax receipt; Fax polling SYSTEM FEATURES ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering Security Functions (standard) and port blocking; SSL2; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 802.1x support; User authentication; Authentication log; Secure print; Kerberos; Hard drive overwrite; Hard drive data encryption (AES 256); Confidential fax receipt; Print user data encryption Security Functions (optional) Antivirus realtime scanning (Bitdefender®); Copy protection (Copy Guard, Password Copy) Accounting (standard) Up to 1,000 user accounts; Active Directory support (user name + - 11

USER BOX SPECIFICATIONS Storable documents

Type of user boxes

	password + e-mail + smb folder); User function access definition
Accounting Functions (optional)	Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (Android/iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

Up to 3,000 documents or 10,000 pages

Group (with authentication)

Public; Personal (with password or authentication);

<sup>1</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

<sup>2</sup> Warm-up time may vary depending on the operating environment and usage

- All specifications refer to A4-size paper of 80  $g/m^2$  quality.

The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

 Some of the product illustrations contain optional accessories.
 Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.

- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

